

Instructions for HP Business Inkjet K550

www.vtechplace.com

Part 1: Package Content

- Ink system - 1 set
- 4 air filters
- 4 syringes
- 4 needles

Part 2: Inspection

- Check whether all the parts are ready. Check the system to see if there is any leak.
- Check the printer status to see whether it is normal or not.
- Print the test sheet on nozzle check to ensure the printer head is in good condition. If everything is okay, then follow the next step.

Part 3: Installation Procedure



Step1:
Open the cover for Inkjet cartridges & remove the original cartridges.



Step 2:
Install the system cartridges according to the color order.



Step 3:
Pull out the small red rubber plugs from the air holes. Then place the air filters into the air holes.

Tip: Save all the rubber plugs and put it in the bag and tape it in the back of your system for future use like moving



Step 4:
Close the cover and use a piece of tape to hold the cover close (the printer will not work if the cover is open).

If this step is not working out well for you, please follow the next step otherwise you are done with the installation process.



Step 5:
Please use a folded like paper that is tapered at the end and insert it into the hole as shown above. This is necessary so that the cartridge cover can be recognized as closed otherwise the printer will not work.

At this point if the printer has any messages that is not normal or does not recognize the cartridges, please turn off your printer for about 30 seconds and switch it back on. It should fix the problem.

Part 4: Operate the Printer



Enter in the Printer Services panel and print a Demo Page.

If it shows any breaks (it maybe caused by air bubbles in the printing head). Please clean your printing head. If it still shows little breaks especially for only one color, please turn off the printer. **It is unnecessary to repeatedly clean the printer-head.** Just keep the printer unused (turned off) for about a few hours and then print a Demo Page again. If it is still abnormal, please kindly contact local dealer.

Part 5: Reset Procedure:

If the indicator light is flashing when printing, it tells that you need to reset the chip to full status. Please turn off your printer for about 30 seconds and switch it back on. Ink meter bar shall show full ink. You can start printing as usual.

Notice:

1. Keep the reservoir bottles on the same level with the printer. If the reservoir bottles are placed at a higher or much lower level than the printer, gravitational leakage of ink may occur. **This is a very important tip.**
2. Try to keep at least a 1/2 inch of ink in the bottles, as you don't want to run out of ink and draw air into the cartridge.
3. Please do not take out the cartridges at random after installing the CIS system.
4. To be used in a dry place between 15 and 35 degree.
5. During transportation of your CIS system please make sure all ventilation and ink filling holes are closed tightly.
6. Do not sway the system frequently as ink leakage may occur.
7. Don't pull out the connectors of the cartridges and do not tear off the adhesive tape at the bottom.

Warning:

1. Keep it out of reach from children. It is not drinkable.
2. Avoid exposure to direct sunlight and don't keep it in high or freezing temperatures.
3. Avoid any collision of the CIS system.